

SPARC® AR

RED DOT





Dual Use: Shooting Tactical / Hunting
Patent Pending

THE SPARC[®] AR RED DOT SIGHT

The rugged, armored SPARC[®] AR with daylight-bright red dot and built in mount is designed to be the ideal companion for the AR platform. Get on target fast with the SPARC AR.





RED DOT ADJUSTMENTS

Battery Installation


Remove the battery compartment cover. Install one AAA battery so the “+” lettering faces inward and replace the cover. When replacing the cover, be sure it is fully screwed down.



Powering Up

To turn the SPARC AR on, press the UP button. To turn the SPARC AR off, press and hold the DOWN button for five seconds.

Note: If you forget to turn off the SPARC AR, it will automatically shut down in approximately 12 hours.





Brightness Adjustments

The SPARC AR red dot sight offers ten variable illumination settings—the lowest two settings being ultra-low for use with night-vision equipment. Adjust the dot brightness by tapping the appropriate UP or DOWN adjustment control button.

Typical Battery Life

The SPARC AR uses a AAA battery. The typical battery life depends on the brightness intensity setting of the dot.

Bright Red Dot	300 Hours	5,000 Hours
----------------	-----------	-------------

Windage and Elevation Adjustments

The SPARC AR red dot incorporates elevation and windage dials with audible clicks. Each small click will move the point-of-impact one Minute of Angle (MOA). 1 MOA will closely correspond to one inch at 100 yards, 1/2 inch at 50 yards, 1/4 inch at 25 yards, etc.

Example

At a 50 yard sight-in distance, it will take twelve clicks of the dial to move the bullet's point-of-impact six inches.

Adjust the elevation and windage settings:

- Remove the dial covers. The battery cover may be used as a tool to loosen and tighten the dial covers
- Use the raised bars on the dial covers, coin or screw driver to make the adjustments.
- Turn the adjustment dial in the appropriate direction as indicated by the arrows. Move the dials in the direction you wish the bullet's point-of-impact to change.

Elevation Adjustment

- Remove the turret cap and turn the inner screw counter-clockwise to adjust the bullet's point-of-impact up; turn the inner screw clockwise to adjust bullet's point-of-impact down.

Windage Adjustment

- Remove the turret cap and turn the inner screw counter-clockwise to adjust the bullet's point-of-impact to the right; turn the inner screw clockwise to adjust windage bullet's point-of-impact to the left.



Mounting the SPARC AR

To get the best results proper mounting is essential. Although not difficult, the correct steps must be followed. Your firearm will need to be equipped with a Picatinny or Weaver style rail/base. If needed, these may be purchased at most firearms dealers. *If you are unsure of your abilities, it would be best to use the services of a qualified gunsmith.*

1. Attach the SPARC AR to the rail/base with the adjustment control buttons facing the shooter and make sure the mount is solidly seated in the base groove. In order to prevent recoil injury, position the SPARC AR so you have at least four inches of eye relief.
2. Be sure the base clamp is hooked around the outside of the rail/base.
3. Press the SPARC AR downward and forward toward the muzzle. Then, firmly tighten the base clamp bolt using the hex wrench.



Position the SPARC AR so you have at least four inches of eye relief.

Note: It is a good practice to regularly re-check all mounting screws (including spacer attachment screws) to be sure they haven't loosened under field conditions.

Mount Height Options

The SPARC AR can be mounted at two heights, lower 1/3 co-witness and absolute co-witness. To mount it at lower 1/3, mount the sight as received. The optic center will be 40mm above the base surface. To mount for absolute co-witness you can remove the 3mm base shim. The optic center at absolute co-witness will be 37mm above the base surface.

To change the mount height, loosen and remove the four base screws and remove the base clamp along with the 3mm shim. Reinstall the base clamp with the four shorter screws supplied with your SPARC AR.





SIGHTING IN

Bore Sighting

After mounting, an initial bore sighting of the SPARC AR at short range (25–50 yards) will save time and money at the range. This can be done using a bore sighter according to the manufacturer's instructions, or by removing the bolt on some rifles to visually sight through the barrel

To visually bore sight a rifle:

1. Place the rifle solidly on a rest and remove the bolt.
2. Sight through the bore and center the target inside the barrel.
3. With the bulls eye centered in the bore, make windage and elevation adjustments until the illuminated dot is also centered over the bulls eye.

Final Range Sight-In

Final sight-in should be done at the range using the exact ammunition you expect to hunt or shoot with:

1. After bore sighting the SPARC AR, fire a shot or two at your desired zero distance to check that you're roughly on target. *If necessary, adjust the dot to put you near the center of the target (see Windage and Elevation Adjustment on page 6).*
 2. Fire a three-shot group as precisely as possible.
 3. Using the center of this group as a reference, make any necessary adjustments for windage and elevation correction. Using arrows for reference, adjust dials in the direction you wish the group to move.
 4. Fire a final three-shot group to confirm proper adjustment. Repeat as necessary.
- Final Range Sight-In



SHOOTING WITH THE SPARC AR

The key thing to remember when shooting with the SPARC AR red dot is to keep both of your eyes open! Shooting with both eyes open allows you to take full advantage of your peripheral vision to get on target very quickly. Eye placement is not critical. As long as you can see the dot, you'll hit your target!

Note: If using an optional magnifier for distance shooting, you may find it easier to shoot with one eye closed due to the increased magnification.

TROUBLESHOOTING

Please check the following before returning the SPARC AR for service.

If the red dot does not illuminate:

- Is the battery dead? Replace.
- Is the battery installed correctly? Be sure the battery is oriented with "+" lettering facing inward.
- Is the battery cover loose? Be sure cover is snug and contact points are clean.

If bullets are not grouping:

- Be sure all mount screws are tight. You should not be able to twist or move the SPARC AR in any direction. Many times, problems thought to be with the scope are actually mount problems.

Note: Our **Troubleshooting Guide** is available online at <http://www.vortex-optics.com/content/troubleshooting>.



MAINTENANCE

Cleaning

The SPARC AR red dot will require very little routine maintenance other than periodically cleaning the exterior lenses. If desired, the exterior may be cleaned by wiping with a soft, dry cloth.

When cleaning the lenses, be sure to use products that are specifically designed for use on coated optical lenses such as the VTX Lens Pen and FogFree Cleaning Kits.

- Be sure to blow away any dust or grit on the lenses prior to wiping the surfaces.
- Using your breath, or a very small amount of water or pure alcohol, can help remove stubborn things like dried water spots.

Lubrication

All components are permanently lubricated, so no additional lubricant should be applied.

Note: Do not attempt to disassemble any components of the red dot.

Storage

Use the included lens cover to protect the lenses when not in use.

- Remove the battery before putting in storage for extended periods.
- Avoid storage in direct sunlight or in any very hot location.
- Storage and use in extreme cold will shorten battery life.

THE VIP WARRANTY

We build optics based on our commitment to your absolute satisfaction. That's why our products are unconditionally guaranteed and we make this Very Important Promise to you—a Very Important Person.

Rest assured that in the event your SPARC AR becomes damaged or defective, we will repair or replace it at no charge to you. Call us at 800-426-0048 for prompt, professional, and friendly service.

2120 West Greenview Drive
Middleton, WI 53562 service@
vortexoptics.com

Visit www.vortexoptics.com for more information. Canadian customers may visit www.vortexcanada.net for customer service information.

Note: The VIP Warranty does not cover loss, theft, deliberate damage or cosmetic damage that does not hinder the performance of the product.



M-00169-0